

DESCRIPTION PRECAUTIONS

CHILL DROP OPAQUE is a highly concentrated colour pigment. Completely compatible with all the products of our CHILL EPOXY line. Strong colours will be achieved by using gradually between 0.0250% up to 5% in weight/volume in the mixture A/B until you reach the desired colour. This pigment meets the European RoHS standard.

CARACTERISTICS

- For use with CHILL EPOXY™ liquid resins.
- Medium viscosity
- Easy use to obtain opaque colours
- Meets the RoHS standard
- Highly concentrated pigments
- 100 % solid reactive pigments
- Vast selection of bright colours: white, light blue, dark blue, brown, light grey, medium grey, dark grey, yellow, purple, mustard, black, orange, red, sand, green, mauve.

APPLICATION

For use with our CHILL EPOXY™ liquid resins.

Store **CHILL DROP OPAQUE on a shelf** (do not store directly on the floor) @ 22 °C with relative humidity less than 60%. A cold environment will increase the viscosity of the pigment and a warmer environment will decrease it.

This is an extremely **concentrated colour** pigment. We suggest the user to determine the amount of pigment to add to the mixture by adding gradually a few drops to the mixture A/B.

Wear latex gloves to prevent staining your hands.

Make sure to shake well before use.

Be sure to wipe the bottle with isopropyl alcohol to keep it clean.

Contact **POLYMERES TECHNOLOGIES** for more information. support@polymerestechnologies.com

TYPICAL PROPERTIES (AT 22°C)

Viscosity	Brookfield (cps)	6457 cps – 13,558 cps
Consistency		Liquid
Density	g/cm ³	1.08-1.37
Type of coloration		Opaque

- Consult Material Safety Data Sheet prior to use.
- Normal health and safety precautions should be observed when handling these products.
- Ensure good ventilation.
- Wear gloves safety glasses and protective clothing.
- Once the container is opened **POLYMERES** has no control or responsibility for the shelf life.
- Shelf life of product in original closed containers is **one (1) year**.

It is recommended to follow Provincial and Federal safety regulations. In case of eye contact, rinse well with water, in case of skin contact, rinse with soap and water. Keep away from children.

GARANTEE

Having no control over the use and application of this product, the manufacturer and / or the distributor cannot guarantee the result obtained. The warranty is therefore limited to the replacement of a product that the user has demonstrated to the satisfaction of the manufacturer and distributor that it is actually defective. Before using this product, the user must ensure that the product is suitable for its intended use. Only the user assumes the risks related to this use. The user must ensure that this product meets his needs by conducting tests in the short, medium and long term to validate the results and in the conditions of use and according to the instructions provided. This limited warranty excludes all liability for consequential, incidental or special damages. Except as described above, the user expressly acknowledges and accepts at the time of the purchase of this product that the manufacturer and / or distributor disclaims any other liability and any other express or implied warranty of quality and an implied warranty of quality of the material are expressly excluded.